

Plasticoate 750 ACRYLCOATING S

Clear / colored acrylic paint, solvent-based
for sealing of concrete roof tiles, bricks, slates art,
Fibreboard and concrete

PLASTI CHEMIE
Produktionsgesellschaft mbH

Proerties:

Plasticoate 750 Acrylic Coating S is distinguished by its ease of processing, excellent weather resistance and durability as well as its high UV resistance and very good resistance to alkalis and acids. It prevents carbonation, is at a sufficiently high coating Waterproof and improves cleaning possibilities. Plasticoate 750 Acrylic Coating has excellent adhesion to various substrates.

Technische Daten:

Chemical basis	Polyisobutylmethacrylat
Delivery form	clear or colored varnish
Solid content	30% Polymer
classification	flammable
Smell	esterlike
Viscosity	32 ± 3 s (im DIN cup, 4mm) at 73.4°F
Density	7.01 lb/gal (68°F)
Flame Point	< 32°F
Dry time	30 Min bei 73.4°F
Cleaning of tools	Aceton, Testfuel
Usage	Exterior paint concrete and fiber-cement boards and cement
storage	1 year – dry and cool (min. 41°F to max. 68°F)

PRODUCT-INFORMATION:

specification Plasticoate 750 Acrylic Coating S is an solvent based acrylic paint.

Usage Examples: On bricks, slate and natural stone Plasticoate 750 Acrylic Coating S is used as a clear or colored sealer to produce a non-porous and waterproof surface. On concrete Plasticoate 750 Acrylic Coating S is used as a clear or colored impregnating agent or as a sealer. It prevents the ingress of water and prevents corrosion and carbonation. By using Plasticoate 750 Acrylic Coating S

Plasticoate 750 ACRYLCOATING S

Clear / colored acrylic paint, solvent-based
for sealing of concrete roof tiles, bricks, slates art,
Fibreboard and concrete

PLASTI CHEMIE
Produktionsgesellschaft mbH

gives an easy-to-clean surface.

- Remark:** Only for industrial use. Apply only on dry surfaces and not just before rain.
Processed at temperatures above 41 ° F.
- packaging:** 180 kg barrel, 25 kg bucket, 10 kg bucket
- colors:** transparent, anthracite, light gray, brick red, white, beige.
- Hints:** Stir well before use!
- Using:** Plasticoate 750 Acrylic Coating S can be applied with a brush, roller or airless spray.
- When applying Plasticoate 750 Acrylic Coating S colored, we recommend one layer transparent and it 2 layers Plasticoate 750 Acrylic Coating S color.
- consumption:** transparent: ca. 0,20 - 0,40 gal/ft.sq (per layer) depends on the substrate
pigmented: ca. 0,40 - 0,60 gal/ft.sq (per layer)
- Consumption depends on the porosity of the surface. Clean tools within 20 minutes after applying the layer with washing fuel or similar means.
- Health- and Safety –**
- Hints:** Product and Safety Data Sheets must be understood and read carefully!

Data concerning our products and devices as well as concerning our data and procedures are based on an extensive research work and an application technology experience. We obtain these results, with which we do not take over adhesion going beyond the respective single contract, in word and writing after best knowledge, reserve ourselves we however technical changes in the course of the product development. That does not relieve the user however to examine our data and recommendations before their use responsible for the own use. That applies also regarding the keeping of patent rights third as well as for applications and procedures, which are not expressly in writing indicated by us.